

MODEL A FORD CLUB OF AMERICA

250 SO. CYPRESS • LA HABRA, CALIFORNIA 90631-5586
562/697-2712 • 562/697-2737

Judging Standards Test Instructions

2016 Revision Tests.

Areas – 5, 9, 10, 11, 12, 13, 15, 17, 20, 21, 23
Early 1928 Vehicles (new), Station Wagons (new),
Mail Trucks (new), Heavy Commercial Vehicles (new), Canadian Model A's,
Cabriolet(new)

2011 Revision Tests.

Areas – 1, 2, 3, 4, 6, 7, 8, 14, 16, 18, 19, 22,
Convertible Sedan (new)

Test Completion Options:

Option 1: All tests can now be completed on your computer (Windows or Mac) using Adobe Reader or Adobe Acrobat (version 5 or newer). *Adobe Reader is a free program and can be downloaded from www.adobe.com.* Use your mouse or tab key to navigate the test pages. Once the tests are completed, save each test file with a new name, example “yourname_area1.pdf”. *Warning: Do not change or alter the .pdf extension.* Finally, email your test files to jstests@mafca.com for processing.

Option 2: Print the test forms as required and complete them by hand, *please print clearly.* Mail your completed tests to:

RG & JS Tests
MAFCA Judging Standards Committee
250 S. Cypress St.,
La Habra, CA. 90631-5515

MODEL A FORD CLUB OF AMERICA

250 SO. CYPRESS • LA HABRA, CALIFORNIA 90631-5586
562/697-2712 • 562/697-2737

Judging Test 23 – Shocks and Shackles

Use 2016 Restoration Guidelines Revisions

Name: _____ Date: _____

Address: _____

Email: _____ Phone No.: _____ MAFCA # _____

1. Shock covers were positioned so that filler plugs were approximately ____degrees from top center.
2. In early 1930, an _____cover was adopted to provide a better seat for the shaft seal.
3. Beginning in 1930, shock arms were redesigned to provide _____ at the shock cover.
4. In addition to Houdaille and Ford, shocks were also manufactured by _____and _____.
5. By mid-1931, all shock bases had a _____backside, which is partly visible on the rear-mounted shocks.
6. All four shocks should be of the same _____and the bases/covers should _____for the same time period.
7. The two basic styles of shock arms had either an _____or a _____forging-die-parting line.
8. Shock link closed end designs are described as: _____, _____, _____, _____or _____.
9. Angled cotter key holes on the spring shackles were used from the beginning of production through (date) _____.
10. “Coined” elongated figure 8 shaped shackle bars were used from (dates) _____through _____.

***** END OF TEST *****