250 SO. CYPRESS • LA HABRA, CALIFORNIA 90631-5586 562/697-2712 • 562/697-2737

Judging Standards Test Instructions

2016 Revision Tests.

Areas – 5, 9, 10, 11, 12, 13, 15, 17, 20, 21, 23
Early 1928 Vehicles (new), Station Wagons (new),
Mail Trucks (new), Heavy Commercial Vehicles (new), Canadian Model A's,
Cabriolet(new)

2011 Revision Tests.

Areas – 1, 2, 3, 4, 6, 7, 8, 14, 16, 18, 19, 22, Convertible Sedan (new)

Test Completion Options:

Option 1: All tests can now be completed on your computer (Windows or Mac) using Adobe Reader or Adobe Acrobat (version 5 or newer). Adobe Reader is a free program and can be downloaded from www.adobe.com. Use your mouse or tab key to navigate the test pages. Once the tests are completed, save each test file with a new name, example "yourname_area1.pdf". Warning: Do not change or alter the .pdf extension. Finally, email your test files to istests@mafca.com for processing.

Option 2: Print the test forms as required and complete them by hand, *please print clearly*. Mail your completed tests to:

RG & JS Tests
MAFCA Judging Standards Committee
250 S. Cypress St.,
La Habra, CA. 90631-5515

MODEL A FORD

CLUB OF AMERICA



250 SO. CYPRESS • LA HABRA, CALIFORNIA 90631-5586

562/697-2712 • 562/697-2737

Judging Test 13 – Sheet Metal Use 2016 Restoration Guidelines Revisions

Name	e: Date:
	ess:
Email	: Phone No.: MAFCA #
1.	Area 13 includes all exterior painted metal panels including the underside of the hood and body.
	(True or False)
2.	The hood louvers were changed in Mid 1928 so that they were parallel to the
	(Body, Location)
3.	Early (1928) hood handles had anrivet on each end of the handles. (Style)
4.	The hood bumper was changed in April 1931 from ashape to ashape.
	(Style, Style)
5.	From December 1928 through the end of production, hood corners were a one piece design made
	with the sewn seam at the (Color, Material, Location)
6.	After,all front fenders had an embossed cup area around the front mounting screws
	(Month, Year)
7.	Original fenders hadcompletely around the rolled edges.
8.	Fender welt material was made of a with a
	core. (Color, Material, Material)
9.	In March 1931, awas stamped into the inside rear skirt of the sedan fender.
10.	The stamped letters "MB" in some 1930-31 rear fenders should match on each fender.
	(True or False)
11.	When did the rumble seat hinges change from forged to cast? (Month, Year)

12.	The 1929 style radiator splash apron hadformed on both the top and bottom edge.
13.	All surfaces on all original front splash aprons had slightlysurfaces. (Style)
14.	The finish of the machine screws attaching the hood shelves to the front splash shield through
	mid 1928 were paintedwhile late 1928 through 1929 were _
	plated. (Color, Finish)
15.	The hood latches were mounted so that the edges of the bracket kept them from falling inward
	throughout production. (True or False)
16.	The matting on 1928-1929 running boards was apattern and awas
	used in 1930-1931. (Style, Style)
17.	From October 1930 through 1931, the underside of the running boards were coated with
	material. (Color, Finish)
18.	Door dovetails wereplated. (Finish)
19.	After February 1928, reinforcing ribs on the rear fender body panels of coupes were eliminated.
	(True or False)
20.	Cowl welting was a smaller diameter than fender welting and was painted lower body color.
	(True or False)
